

Турбинные расходомеры газа серии НО

Технические характеристики



Архангельск (8182)63-90-72
Астана +7(7172)727-132
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Казань (843)206-01-48

Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41

Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93



TECHNICAL DATA SHEET

OUTSTANDING FEATURES

- Low cost.
- Outstanding accuracy.
- Provides wide flow ranges.
- Wide variety of process connections available.*
- Operate over a wide range of temperatures and pressures.
- Exclusive use of hybrid ceramic ball bearings provide superior life.

*MS Flared or Flanged end connections are best suited due to the even transition at the connections.



GAS SIZE SELECTOR CHART FOR STANDARD HO SERIES TURBINE FLOWMETERS

Flowmeter Size Diameter (inches)	Repeatable Range** Based on a Gas Density of 1# /Ft ³		Repeatable Range** Based on a Gas Density of .25# /Ft ³	
	Magnetic Coil (ACF/M)	MCP Coil (ACF/M)	Magnetic Coil (ACF/M)	MCP Coil (ACF/M)
1/2 x 1/4	N/A	.15 – 3.5	N/A	.3 – 3.5
1/2 x 3/8	N/A	.3 – 5	N/A	.6 – 5
5/8	N/A	.5 – 10	N/A	1 – 10
3/4	N/A	.6 – 20	N/A	1.2 – 20
1	2.5 – 43	.8 – 43	5 – 43	1.6 – 43
1 1/4	3.5 – 100	1.25 – 100	7 – 100	2.5 – 100
1 1/2	5.0 – 120	1.75 – 120	10 – 120	3.5 – 120
2	10 – 200	3.5 – 200	20 – 200	7 – 200
2 1/2	15 – 500	5 – 500	30 – 500	10 – 500
3	20 – 600	7.5 – 600	40 – 600	15 – 600
4	30 – 1100	N/A	60 – 1100	N/A
5	40 – 1800	N/A	80 – 1800	N/A
6	50 – 3000	N/A	100 – 3000	N/A
8	100 – 4800	N/A	200 – 4800	N/A
10	150 – 7500	N/A	300 – 7500	N/A
12	200 – 12000	N/A	400 – 12000	N/A

This chart is for quick reference only and not for final size. Calculate using actual service conditions.

**Lower limit of flow range is dependent on user's operating density.

SPECIFICATIONS

Overrange: 150% of maximum flow (intermittently).

Available Turn Down Range: Dependent on gas density at user's operating conditions.

Linearity: ±1% of reading typical. ***

Repeatability: ±0.25% over tabulated repeatable range.

Note: Performance enhancement techniques are routinely applied to produce wider linear and useable flow ranges. This technique is also used to improve linearity and repeatability. Consult the applications group at Hoffer with your requirements.

Available Temperature Range: -450°F to +300°F continuous (to +400°F intermittent heat). Dependent on bearing/coil selection.

End Fittings: MS flared and flanged styles are recommended. Other types available on request.

Bearing Styles: Self-lubricating, ceramic hybrid ball bearings.

Materials: 316/316L dual rated stainless steel standard. Consult with applications group for corrosive applications. Broad material list available.

***Linearity is density-dependent for a given meter. Consult factory for details.

GAS TURBINE FLOWMETER MODEL NUMBERING SYSTEM

MODEL HO (A) X (B) - (C) - (D) - (E/F/G) - (H) - (I)

A. End Fitting Size

B. Flowmeter Size

C. Blade Angle (See Note 1)

D. Bearing Type

(BP) Self-lubricating, **ceramic** hybrid ball bearings, sizes 1/4" thru 1".

(CB) Self-lubricating, **ceramic** hybrid ball bearings, sizes 1-1/4" thru 12".

E. Pickup Coils

(1M) One Magnetic Coil

(2M) Two Magnetic Coils

(1MC3PA) One RF Coil

(2MC3PA) Two RF Coils

(1MC3PAHT) One High Temp RF coil

(2MC3PAHT) Two High Temp RF coils

(1HTM) High Temperature Magnetic Coil

(2HTM) Two High Temperature Magnetic Coils

(1ISM) Intrinsically Safe Mag Coil

(2ISM) Two Intrinsically Safe Mag Coils

(1ISM-ATEX) One ISM ATEX coil

(2ISM-ATEX) Two ISM ATEX coils

(RP) Redi-Pulse Coil (See Redi-Pulse Technical Data Sheet RP-XXX)

_() Intrinsically Safe Redi-Pulse Coil (See I.S. Redi-Pulse Technical Data Sheet IRP-XXX)

(P) Pigtail or Flying Leads, Add-P and the Length of leads after any coil except the high temperature coils.

(-ATEX) Add after coil part no. when using ATEX enclosure mounted on meter.

F. Coil Spacing, Mechanical Degrees Apart

() Factory Assigned. Spacing required when meter has two pickup coils. If second coil not required skip option (F).

G. Riser and Explosion-Proof Coil Enclosures

(X) 1" MNPT riser, welded to body. Required for all types of enclosures.

(X-ATEX) 3/4" MNPT riser, welded to the body.

(XE2) 1" MNPT riser with E2 enclosure. (See Chart)*

(X-ATEX)E2 3/4" MNPT riser with E2 enclosure. (See Chart)*

(X8S) 8" Long S/S 1" MNPT riser. (For fluid temperatures below -40°F (-40°C) or above +140°F +60°C).

(X8S-ATEX) 8" Long S/S 3/4" MNPT riser. (For fluid temperatures below -40°F (-40°C) or above +140°F +60°C).

*E2 EXPLOSION-PROOF/FLAME-PROOF ENCLOSURE WITH 3/4" FNPT MOUNT AND 3/4" CABLE ENTRY RATINGS:

FM: CLASS I, DIV. 1, GR. ABCD, CLASS II/III, DIV. 1, GR. EFG, TYPE 4X
CSA: CLASS I, DIV. 1, GR. ABCD, CLASS II, DIV. 1, GR. EFG, CLASS III, TYPE 4X EX D IIC, CLASS I, ZONE 1, IP 66
ATEX: EX II 2GD Ex d tD IIC, IP66/68
IEC: EX D IIC IP68

H. End Fitting Types

(MS) 37 Deg. Male Flare Per MS33656

(NPT) Male National Pipe Thread (See Note 3 below)

(F_) Raised Face Flange per ANSI (See Chart **)

(DN_/PN_CS/SS) DN=Metric size, PN=Flange pressure rating (in DIN std.) and select material

(W_) Wafer Style Body (Use 1, 3, 6, 9, 15 or 25 after "W" to indicate flange weight wafer meter will be used with)

**Pressure Rating/Flange Material

Include "F", number indicating pressure rating, and flange material. (i.e., -F1SS-)

Select one:

- (1) 150# Flanges
- (3) 300# Flanges
- (4) 400# Flanges
- (6) 600# Flanges
- (9) 900# Flanges
- (15) 1500# Flanges
- (25) 2500# Flanges

Select One:

- (SS) Stainless Steel
 - (CS) Carbon Steel
- Note:** 316/316L SS flanges are standard, add-304 at end of model # if 304 flanges are required.

I. Special Features

(CE) CE Mark - Required for Europe.

(PED-CE) PED Mark - Required for Europe.

(SEP-CE) Sound engineering practice.

(PT) 1/4" FNPT Pressure Tap (AGA Compliant).

(PG) Premier Gas turbine for improved accuracy of ±0.5%, requires actual or natural gas calibration. Please see HO-PG-100 for more information.

(SP) Any special features that are not covered in the model number, use a written description of -SP.

(EXP) CSA Explosion-Proof Certification. (See Chart)***

(X) No Special Features

*** CLASS I, DIV. 1, GR. ABCD; CLASS I, DIV. 2, GR. ABCD; CLASS II, DIV. 1, GROUPS EFG
CANADA: CLASS I, ZONE 1 & 2, Ex d IIC
USA: CLASS I, ZONE 1 & 2, AEx d IIC

Request HO-L-110 Technical Data Sheet for complete specifications for HO Series for Liquid Service.

Notes:

1. Blade Angle determined by density, assigned by factory or use of gas sizing program.
2. Turbine sizes 1/4" through 3/4" must be equipped with MC3PA coil. 1" through 3" may be recommended for MC3PA coil depending on gas density and desired turndown range.
3. NPT not recommended for gas service due to possible uneven transition at NPT connections.



The specifications contained herein are subject to change without notice and any user of said specifications should verify from the manufacturer that the specifications are currently in effect. Otherwise, the manufacturer assumes no responsibility for the use of specifications which may have been changed and are no longer in effect.

The quality system covering the design, manufacture and testing of our products is certified to International Standard ISO 9001.



По вопросам продажи и поддержки обращайтесь:

Архангельск (8182)63-90-72
Астана +7(7172)727-132
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Казань (843)206-01-48

Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41

Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Единый адрес для всех регионов: hfr@nt-rt.ru || www.hoffer.nt-rt.ru



HOFFER FLOW CONTROLS, INC.

The specifications contained herein are subject to change without notice and any user of said specifications should verify from the manufacturer that the specifications are currently in effect. Otherwise, the manufacturer assumes no responsibility for the use of specifications which may have been changed and are no longer in effect.

The quality system covering the design, manufacture and testing of our products is certified to International Standard ISO 9001.

